

U-Cars

Car

- Stock body 1980 or newer front wheel drive four cylinder passenger cars only. No all wheel or wheel steering allowed. No vans, pick-up or V6s allowed

Engine/ Transmission

- **NO TURBO OR SUPER CHARGED ENGINES ALLOWED!!** Must be stock type engine for car.

- All engine must remain stock to car model. No Bolted on, wire up, or plugs in aftermarket parts allowed.

- May run header

- May run cold air intake, air cleaner must remain under hood.

- May run after market timing gear. Must be set at 0 degree. stock timing at all times.

- Stock rev limiter must work and be at stock.

- Stock type transmission, may be auto or manual, may be locked if wanted.

- G. May run 110 Octane fuel. **NO ALCOHOL OR NITRO.**

Body

- Minimum weight 2300lbs after race.

- Aftermarket parts allowed however must remain stock appearing.

- All glass removed from car. There must be a minimum of 3 vertical bars in front of the driver. Wire screen recommended.

- All flammable parts inside car, under hood, and in trunk must be removed.

- Doors must be welded or bolted shut.

- Hood and trunk must be secured with a minimum of 2 lock pins.

- No holes cut in the hood. No sharp ends on bumpers allowed.

- **NO DOOR/RUB BARS ON OUTSIDE OF THE CAR.**

Suspension

- No more than 5 degree camber on each tire.

- Any spring in stock location. Non-adjustable, No coil overs, No weight jacks.

Wheels/ Tires

- Stock wheels or stock size race wheels may be used. Must be no more than 7" wide. All four wheels must be same size and offset.

- D.O.T with minimum 400 tread wear or better. No type of racing tire allowed. No snow, mud, or off-road tire allowed.

- **NO STUDED TIRES ALLOWED!!!!!!!** (If you show up with studded tires you will not be allowed to be on the track until your tires are changed. This is for safety

of other drives, fans and track crew.)

Safety

- Aluminum racing seat with a minimum 5 point harness required*
- Fire Extinguisher with gauge required.*
- Cars must have driver side window net.*
- If stock fuel tank is ahead of rear axle, it may be used. If tank is behind rear axle it must be removed and replaced with a maximum 8 gallon fuel cell, enclosed in steel can.*
- Minimum of 4 and maximum of 6 point cage with 3 driver side and 2 passenger side door bars required. Cannot go through the firewall.*
- Fire suit, racing gloves, and racing shoes required. Neck brace suggested and mandatory for all drivers under 16 years of age.*
- Must be able to maintain a safe lap speed to race in the feature race.*

Requirements

- Receivers and Transponders are required at all times.*

Post-Race Tech

- Top 5 cars must go to tech, after race is done.*
- Cars must make weight of 2300lbs.*
- Must pass visual look over.*
- No Claim rule.*